

# DZ-GX5060E

## DVDCAM

30x Optical zoom /  
1500x Digital zoom

EIS Electronic Image  
Stabilisation to ensure  
smoother recordings

Multiformat+ DVD  
burner for superior  
compatibility with DVD  
media and DVD players

**MULTI FORMAT+**  
DVD-RAM/DVD-RW/DVD-R/+RW/SD

One Second Quick Start  
from Standby - ready to  
shoot instantly so you will  
never miss a moment.



HITACHI

MULTI FORMAT+

HITACHI

DVD-RAM/-RW/-R/+RW/SD

DVDCAM



USB 2.0 for high speed  
data transfer to PC



SD card slot for digital  
still photos & photo  
capture from DVD

2.7" True 16:9 widescreen  
LCD screen - what you see  
is exactly what you'll get

## MULTIFORMAT+ DVD Camcorder

Introducing the latest DZ-GX5060E DVD CAM with 30x optical and 1500x digital zoom, Multiformat+ for superior compatibility with DVD media and DVD players and 1-Second Quick Start from standby so you'll never miss a moment.

Additional features are a unique photo capture from DVD function, SD card slot for digital still images, USB 2.0 PC connectivity and true 16:9 widescreen recording so what you see is exactly what you'll get. The DZ-GX5060E offers true sophistication and style in a compact size.

**HITACHI**  
Inspire the Next

# DZ-GX5060E

## DVDCAM



## DZ-GX5060E Technical Specifications

### KEY FEATURES

- 30x Optical Zoom
- MultiFormat+ DVD-RAM/-RW/-R/+RW (& SD Card)
- USB2.0 terminal
- 1-Second Quick Start
- Digital photo mode & photo capture from DVD (to SD card)
- Full Auto Button
- Quick menu

### CAMERA

Lens type	High quality multi coated video lens
LCD	2.7" (16:9 Widescreen) (123k Pixels)
EVF	Colour (200k Pixels)
Optical/Digital zoom	30x/1500x
CCD Image Sensor (Pixels)	Total 0.8M, Movie 410K, Still 410K
CCD size	1/6
Lens F No.	F2.0 – 4.1
Optical zoom focal length (equivalent 35mm)	Movie (4:3) 40.7 – 1221mm Movie (16:9) 39.5 – 1184mm Still 40.7 – 1221mm
Filter diameter	34mm
LCD Video light	●
Built-in flash	–
Accessory shoe	–
EIS (Electronic Image Stabilisation)	●
Minimum illumination	0.3 Lux w/Low light mode
Focus	Auto/Manual
White balance	Auto/Set/Outdoor/Indoor
Iris	Auto/Manual
Recording scene modes	Auto/Sport/Portrait/Spotlight/Sand & Snow/Low Light

### RECORDING CAPACITY

Recording Media DVD	DVD-RAM/-RW/-R/+RW
Movie Formats/Recording Times	Maximum recording time (DVD dual sided) XTRA: 36min./FINE: 60min./STD: 120min.

### GENERAL

Audio Format	2ch Stereo Dolby Digital
Still Image (Picture size)	JPEG 640 x 480
DCF	●
Photo capture from DVD frame to JPEG	●
Start-up time	1-Second Quick Start (1 sec*) Start-up ** (3 sec)
Connectivity	AV/S output AV input USB (with USB cable)
Finalise button	●
Quick Menu (Easy Menu System)	●
Full Auto Button	●
Memory card slot	SD
Display language text	English/French/Spanish/Italy/German/Chinese
Scene Transitions	White/Wipe/Mono
Battery life*** (w/o LCD)	85min
Power consumption (w/o LCD)	3.2W
Supplied battery	DZ-BP07P

### ACCESSORIES

Battery pack	Li-ion 680mAh (1hr)
AC adaptor	AC adaptor/charger
USB PC Cable	●
PC software	CD-ROM for Windows/Macintosh
Shoulder strap	●
AC power cord	●
DC power cord	●
AV cable	Multi connector W/S terminal
Lens cap	●
Instruction manual	●
Quick guide	●
Battery for remote	–
Remote controller	–

### PHYSICAL

Dimensions (W x H x D)	63 x 91 x 132mm
Weight (w/o battery)	420g

HITACHI DIGITAL MEDIA, Hitachi Europe Ltd, Whitebrook Park, Lower Cookham Road, Maidenhead, Berkshire SL6 8YA UNITED KINGDOM  
Tel: +44 (0)1628 585 000 Fax: +44 (0)1628 585 500 www.hitachidigitalmedia.com

The specification above and photography is for reference only and may be subject to change.

\*Using restart mode \*\*Turn on after initialised \*\*\*FINE mode recording

Windows® 98, ME, 2000, XP is a trademark of Microsoft Corporation. Pentium®, Celeron® is a trademark of Intel Corporation. The USB - IF Logos are Trademarks of Universal Serial Bus Implementers Forum, Inc. SD logo is a trademark. All other company and product names are trademarks of their respective corporations. The specification above and photography is for reference only and may be subject to change.