HITACHI Inspire the Next

42PD9700

106cm Visible PLASMA

STER ME

Hitachi's new 106cm visible Plasma Widescreen Television combines PICTURE MASTER HD Technology with stunning design. Offering a whole range of features, this outstanding IDTV Plasma will fit perfectly into any environment.

- 106cm Visible Plasma Widescreen Television
- PICTURE MASTER HD Technology
- Integrated Digital Television (IDTV Built-in)
- HD Ready
- New H⁶ 1080 Alis Panel (1024 x 1080)
- Panel Luminance of 1400cd/m²
- Contrast Ratio 4000:1
- 2 HDMI Sockets
- 3 SCART Sockets
- USB Terminal + SD Card Reader
- Motorised Swivel Stand
- 1200 Text Pages















When only the very best will do, the 42PD9700 is the choice for you. Suited to any environment, particularly in open spaces. With its built-in motorised swivel stand, you get perfect viewing and crystal clear sound from wherever you're sitting – or standing.



The 'HD ready' Logo is a trademark of EICTA HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

PICTURE MASTER

Hitachi's PICTURE MASTER Technology, like all the best ideas, is easily explained. But behind the elegant simplicity of our flat panel TVs, there's a lot going on.

For Standard Definition material, Full Digital Signal Processing and Scaling ensures that the signal remains pure and clean, while High Quality Digital Image Pixel Processing Technology analyses every pixel in each image signal. Two hi-tech chips work together to handle the process.

Firstly, the new 1080 Progressive Processing system up-scales incoming signals, adding extra pixels to create unparalleled sharpness and detail to our HD ready panels. Then the Super Dynamic Contrast function analyses pictures to enhance picture quality in dark scenes and provide even richer blacks. For HD 1080 broadcasts the new Picture Master HD processor can display all 1080 lines without scaling ensuring the highest possible quality pictures.

In addition, Hitachi Plasma TVs boast 68.6 billion colours thanks to the 12-bit Advanced Digital Colour Management which reproduces 4093 colour graduations. Finally, there's the High Quality Video Motion processing system, with a High Speed Calculation process which controls every on-screen pixel to avoid any blurring.

Hitachi's unique technology gives our 9700 Series state-of-the-art picture quality.

HDTV (High Definition Television)

ESOLUTION

Starting in Europe in 2006, HDTV will offer the best TV picture quality ever seen. At present, most people use either an analogue signal or a standard definition digital signal (SDTV) to receive broadcast television. HDTV will be a step beyond even the great improvement of digital SDTV.

WEED COLOUR

HDTV uses many more pixels than present services offer, creating the strongest and most detailed TV image you can have. It's far sharper than a DVD is at present.

The majority of Plasma Televisions sold today are not HD ready. But thanks to Plasma and LCD technology from Hitachi, you can now future-proof your purchase by choosing a TV that is fully compatible with the new standard. Only HD ready panels such as ours will be capable of displaying high-definition digital sources.

Thanks to our revolutionary flat screen technology, Hitachi flat panel displays are the ideal choice if you're thinking of investing in a TV today. You need a display that's ready to cope with the extra demands that HDTV puts on your equipment – and ours are.



Standard Resolution







ready

H⁶ Plasma Panel

With a palette of up to 68 billion colours, the $H^{\rm g}$ Plasma Panel provides high contrast levels to bring the most vivid colours to life.

42PD9700

106cm Visible PLASMA





Technical Specifications

GENERAL		SIGNAL INPUT AND	TERMINALS	
Power supply	AC100-240V	RGB Input		RGB : Mini D-sub 15-pin
Frequencies	50/60 Hz			Audio : Stereo mini jack
Power consumption	370W	Control terminal		Service use only (RS-232C : D-sub 9-pin) Female
	<3W (stand-by)	Video Input		Video1 (CVBS/S, L+R) : 21-pin SCART
Dimension (W x H x D)	1134 x 648 x 98mm (excluding stand)			Video2 (CVBS/SCART-RGB, L+R) : 21-pin SCART
	1134 x 728 x 350mm (including stand)			Video3 (CVBS/SCART-RGB, L+R) : 21-pin SCART
Weight	37.3kg (excluding stand)			Video4 (CVBS/Y,Pb,Pr, L+R) : RCA pin
	43.0kg (including stand)			Video5 (CVBS/S-video, + L+R) : RCA pin (Side Inpu
Stand (Option)	Power Swivel			HDMI1 (Video)
DISPLAY CHARACTERISTICS				HDMI2 (Video) +3.5mm Stereo Mini Jack
Effective display area (H x V)	922 x 522mm, (1059mm) diagonal	Photo Input		• USB & SD
Aspect ratio	16:9	SIGNAL OUTPUT		
Number of pixels (H x V)	1024 x 1080 pixels (A4 ALIS)	Headphone		•
Pixel pitch (H x V)	0.90 x 0.485mm	Sub woofer out		
Number of colours (gray levels)	68.6 billion colours (1024 gray scale)	A/V output		1 (CVBS+L/R) : RCA pin
Transmission of front filter	36%	PICTURE		1 (012012/11/110/1pin
Brightness (at white peak)	Panel brightness : 1400cd/m ²	Comb Filter		3D Y/C Comb Filter
Contrast ratio (Panel)	4000:1 Typical	Noise Reduction		
INPUT SIGNAL		LTI/CTI		•
RE	V/U/Cable/Hyperband	AVL		 (Perfect Volume)
	PAL B, G, H / I / D, K	Picture mode		 (reflect volume) 3 (Dynamic, Natural, Cinema)
Signal	SECAM B, G/D, K/K1/L, L'	White Balance		4 (Cool, Normal, Warm, Black & White)
RF Multiplex	A2/NICAM	Dynamic Contrast		
Text	AZ/NICAM 1200 pages	Colour Management		•
Video Signal	PAL/SECAM/PAL60/NTSC4.43/NTSC3.58/	Film Mode		•
video Signai	PAL/SEGAWI/PALOU/NTSC4.43/NTSC3.58/ PAL-M/PAL-N/SCART RGB			•
Component Signal	480i/p, 576i/p, 720p(50/60), 1080(50/60)	SOUND		000 10000
HDMI Signal Video mode	480i/p, 576i/p, 720p(50/60), 1080(50/60), VGA	Surround		SRS WOW
Analog RGB Signal	VGA-UXGA (15kHz, 30 to 106kHz, 50Hz to 85Hz)	Correction		BBE
INPUT SIGNAL (DIGITAL TUNER PART)		Sound mode		4 (Movie, Music, Speech, Favourite)
Digital tuner	•	Audio Power (RMS)		36W 3 way 10 speakers
Digital Teletext (MHEG 5)	 for "U" version 	OPERATION		
DIGITAL REFERENCE (MILEG S)	• 101 O Version • (7days)	OSD Languages	Analogue TV	UK, SW, NO, FIN, DA, CZ, POL, HUN, SLO, CRO
Program Reminder & Event timer	- (/uays)		Digital TV	UK, FR, GE, SP, IT
Multi Language Subtitle Decoding and Display	•	Timer (Off/On)		•
ininin ranguage Subrine Decouning and Dispiray	•	Multi picture function		PIP
		Wide Mode (Picture size)		TV/Video 5-mode PC 5-mode
			TV/Video	Panoramic, Zoom, Cinema, Full, 4:3
			PC	Full, Real, Normal, Zoom1, Zoom2, Zoom3
		Side Input		•
		Switches/buttons		Main Power Switch, Sub Power Switch
				Program Up/Down, Volume Up/Down
				Monu Input coloct













Menu, Input select