

P50T01 127cm Visible PLASMA



T SERIES

The P50T01 is the flagship model of the new T series, using a new elegant design and a host of amazing features. Combined with the Hitachi ALiS 1080 panel and Picture Master FHD engine this TV provides state of the art picture quality and an outstanding viewing experience.

- 127cm Visible Plasma Widescreen Television
- High Resolution of 1280 x 1080 Pixels
- PICTURE MASTER FHD Engine
- Integrated Digital Television (IDTV)
- 2 x HDMI Sockets
- 3 x SCART Sockets
- Optical Audio Output Terminal
- SD Card Reader
- USB Socket
- 2000 Page Teletext
- Multi Picture Modes
- Power Swivel Stand



HITACHI
Inspire the Next

P50T01



P50T01 Technical Specifications

PICTURE

| | |
|---------------------------|------------------------|
| Screen Size | 50" (127cm V) |
| Screen Type | PDP |
| Resolution (Pixels) | 1280 x 1080 |
| Advanced Image Technology | PICTURE MASTER Full HD |
| Panel Luminance (Typical) | 1300cd/m ² |
| Contrast Ratio | 10,000:1 |
| HD Ready | ● |
| PaP/PaT/PinPC | ●/●/- |
| Pixel Pitch (HxV) (mm) | 0.86 x 0.58 |
| Aspect Ratio | 16:9 |

TUNER

| | |
|-------------------------------|---------|
| Programmes (Analogue/Digital) | 200/500 |
| Cable/Hyperband | ● |
| VHF | ● |
| UHF | ● |
| Text Pages | 2000 |

VIDEO SIGNAL INPUT

| | |
|---------------|-----|
| PAL/PAL60 | ● |
| SECAM | ● |
| NTSC4,43/3,58 | ●/● |
| 1080p 50/60 | ●/● |
| 1080i 50/60 | ●/● |
| 720p 50/60 | ●/● |
| 576p/576i | ●/● |
| 480p/480i | ●/● |

VIDEO CONNECTIONS

| | |
|----------------------------------|-------------------------|
| HDMI Input (HDCP) | 2 (1 x Front, 1 x Rear) |
| SCART Socket (RGB) | 3 (2) |
| Component Video | ● |
| Progressive Input (PAL/NTSC) | ●/● |
| S-VHS Video | ● |
| Composite Video | ● |
| Video Line Out (Phono) | ● |
| Video Line Out (Tuner via SCART) | ● |
| SD Card Reader | ● |
| USB Socket | ● |

AUDIO

| | |
|-------------------|-----------------|
| RMS Output | 20W |
| Sound Effect | BBE, SRS, Focus |
| TRUBASS | ● |
| 1 Bit Digital Amp | - |
| Dynamic Bass | - |

AUDIO CONNECTIONS

| | |
|-------------------|---|
| Optical Audio Out | ● |
| Audio Input | ● |
| PC Audio Input | ● |
| Audio Line Out | ● |
| Headphone Socket | ● |

COMPUTER INPUT

| | |
|---------------|---|
| RS232 | ● |
| 15 Pin D-sub* | - |

GENERAL

| | |
|---|--|
| Power Consumption/Standby | 451W<0.8W |
| Weight (inc stand and spkrs) | 47Kg |
| Weight (exc stand and spkrs) | 41Kg |
| Dimensions (W x H x D) (mm) (inc stand and spkrs) | 1240 x 882 x 423 |
| Dimensions (W x H x D) (mm) (exc stand or spkrs) | 1240 x 821 x 128 |
| Swivel Stand/Motorised | Motorised swivel stand |
| OSD Languages | ENG/GER/FRE/SP/IT/SWE/NOR/FIN/DAN/DUT/ GRE/POR/TUR/CZE/POL/HUN/SLO/CRO/ROM |
| IB Languages | ENG/FRA/GER/ESP/ITA |
| Hotel Mode | ● |

IDTV-DVB INTEGRATED

| | |
|--|-----|
| Tuners | 1 |
| Digital Teletext | ● |
| Interactive Services | ● |
| EPG (now next/7 Day) | ●/● |
| Programme Reminder & Event Timer | ●/● |
| Multi Language Subtitle Decoding and Display | ● |
| CA Socket | ● |

CERTIFICATION

| | |
|----------|---------------|
| Safety | ● |
| EMI | ● |
| CE | ● |
| EAN Code | 4902530792935 |

*PC Input is available via HDMI from a DVI output socket on the PC.
The following resolutions are supported: 640 x 480/60Hz, 1024 x 768/60Hz, 1280 x 768/60Hz and 1366 x 768/60Hz



HITACHI DIGITAL MEDIA, Hitachi Europe Ltd, Whitebrook Park, Lower Cookham Road, Maidenhead, Berkshire SL6 8YA UNITED KINGDOM
Tel: +44 (0)1628 585 000 Fax: +44 (0)1628 585 500 www.hitachidigitalmedia.com

The specification above and photography is for reference only and may be subject to change.
The "HD ready" Logo is a trademark of EICTA

HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.